Sanitary Diaphragm Valve Configuration Selection Sheet

Make one selection per valve configuration

	Main Valve:	Port or Port Valve:
Tag Number:		
1. Size	.05	.05
2. Connection	1 2	3
Clamp	☐ ☐	☐
Butt-weld	€ €	€
Butt-weld extension	€ €	€
3. Body Finish		
Electropolish	€	€
150 grit 30-35 Ra µin.	€	€
180 grit 20-25 Ra µin.	€	€
240 grit 15-20 Ra µin.	☐	☐
320 grit 9-11 Ra µin.	€	€
4. Diaphragm	€	€
EPDM	☐	☐
PTFE	€	€
Viton	€	€
Other		
5. Manual Actuation Type		
Stainless Steel	☐	☐
Plastic	€	€
Cast Iron	€	€
Travel Stop	€	€
Locking Bonnet	€	€
6. Automated Actuation Type		
Fail Close	€	€
Fail Open	€	€
Air to Air	€	€
Solenoid	€	€
7. Accessories		
Electrical Indication	€	€
Optical Indication	€	€
Stroke Limiter	€	€
SL w/ Indicator	€	€
Manual Override	€	€

SPECIAL

Valve Port Configuration:

Valve vertical, port horizontal | Valve horizontal, port vertical | Valve horizontal, port horizontal

CON A ☐ 

CON B ☐ 

CON C ☐ 

CON D ☐ 

CON E ☐ 

CON F ☐ 

Cluster Valve Configuration:

Main valve in the vertical orientation, port valve in the horizontal orientation

CON 01 ☐ Top Left 

CON 02 ☐ Top Right 

CON 03 ☐ Bottom Right 

CON 04 ☐ Bottom Left 

Main valve in the horizontal orientation, port valve in the vertical orientation

CON 05 ☐ Left Back 

CON 06 ☐ Right Back 

CON 07 ☐ Right Front 

CON 08 ☐ Left Front 

Both main and port valve in the horizontal orientation

CON 09 ☐ Right Right 

CON 10 ☐ Left Left 

CON 11 ☐ Right Left 

CON 12 ☐ Left Right 

GEMÜ® VALVES, ACTUATORS AND CONTROL SYSTEMS

3800 Camp Creek Parkway • Building 2600, Suite 110 • Atlanta, GA 30331 • Phone (404) 344-8970 Fax (404) 344-9350 • www.gemu.com