
SANITARY BUTTERFLY





Tri-clamp Ends D P 8 C C



THE WILLIAMS - CARVER COMPANY, INC. 4001 MISSION RD P.O. BOX #3140 KANSAS CITY, KS 66103-0140 e [913] 236-4949 Fax [913] 236-9331 www.williamscarver.com

FEATURES/SPECIFICATIONS:

- -ASTM 316L grade stainless steel material
- -Surface finish meets all 3-A, FDA & USDA standards and requirements
- -316L mirror finish disc helps provides an even flow preventing obstructions and restrictions
- -The Tru-Flo butterfly valve featrues a special "opposing" body bolt design that prevents the loosening between body sections due to vibration and usage. This positive sealing prevents the usual leaking and maintenance worries that are common in other sanitary butterfly valves.
- -Body bolting is flush with the body's surface preventing obstruction or modifications needing to be made to the valve during actuation or when space is limited for installation
- -FDA approved Silicone, EPDM, Viton, and White Viton Seals are available
- -Special 304ss 13-position, spring loaded, lever lock handle
- -Standard Connections are Tri-Clamp and Butt-Weld. Other end connections are available upon request
- -Suitable for actuation with pneumatic, electric and canister
- -Pressure 110 PSI @ 200 degrees F. (Approx. 95C)

TRI-CLAMP (STANDARD)					
size	Α	В	С	D	L
1.0"	22.1	50.5	44.5	79	61
1.5"	34.8	50.5	44.5	85	64.3
2.0"	47.5	64.0	47.6	105	74.3
2.5"	60.2	77.5	48.4	112	77.6
3.0"	72.2	91.0	51.5	125	84.3
4.0"	97.6	119.0	60.8	157	101.6
6.0"	148.3	166.9	76.2	208.3	76.2

Description	Material	Qty
Body Half	316L	1
Disc	316L	1
Seal	Silicone/EPDM/Viton	1
Body Bolts	304	1
Notch Plate	304	1
Body Cap	Buna	1
Handle Cap	Buna	1
Handle Screw	304	1
13 Position Handle	304	1

SHORT BUTT - WELD (STANDARD)					
size	Α	В	С	D	L
1.0"	22.1	25.4	25.4	87.0	61
1.5"	34.8	38.1	25.4	97.0	64.3
2.0"	47.5	50.8	25.4	110.0	74.3
2.5"	60.2	63.5	25.4	110.0	77.6
3.0"	72.2	76.2	31.8	127.1	84.3
4.0"	97.6	101.6	31.8	160.0	101.6

Note: 6" Weld End also available

LONG BUTT - WELD (SPECIAL)					
size	Α	В	С	D	L
1.0"	22.1	25.4	34	79	61
1.5"	34.8	38.1	38	85	64.3
2.0"	47.5	50.8	40	105	74.3
2.5"	60.2	63.5	40	112	77.6
3.0"	72.2	76.2	41	125	84.3
4.0"	97.6	101.6	44	157	101.6

BFY- 316L