





The W70 offers series Mix Proof valves to allow flow of two different media through the same valve simultaneously, without the potential for mixing. W70 series valves are excellent tools for automating pipeline processes.

- 1" through 6" tube size and Sched. 5 pipe sizes.
- Sturdy, machined from bar spherical bodies. One piece or two piece body construction available.
- W71, W73 double compression set design.
- W72RS, W75RS, W75CP radial seal (minimum leakage) design.
- A wide choice of arrangements, controls, and options are available to meet process requirements.




- W75CP PMO Mix Proof for dairy applications; compliant for seat-lift cleaning
- W72RS Tank Outlet valves
- Mix Proof valve lifter available





W70 Series Mix Proof Valve Features:



Flexible Control Options in a NEMA 4X Module with Clear Top and Heavy **Duty Stainless Steel Base**

Maintainable Actuator with Safety-Caged Stainless Steel Springs

Stroke Alignment and Stem Support from (6) PTFE Bearings

Strong, machined-from-bar bodies are free-draining and CIP cleanable

Finger safe yoke area, no pinch points during actuation

Lower balancer to protect against water hammer

Secure Mix Proof protection between upper and lower ports Both Radial Seal and Compression Seal Designs Available

Upper balancer options to protect against water hammer when flowing top to bottom Removable Lower Bearing and Seal Carrier









PROCESS EQUIPMENT



Your local contact:



THE WILLIAMS - CARVER COMPANY, INC.

4001 MISSION RD P.O. BOX #3140 KANSAS CITY, KS 66 103-01-0 Office (913) 236-4949 Fax (913) 236-9331

SPX Process Equipment 611 Sugar Creek Road

Delavan, WI 53115

Phone: (262)728-1900 or (800)252-5200 Fax: (262)728-4904 or (800)252-5012

E-mail: wcb@spx.com

For more information about our worldwide locations, approvals, certifications, and local representatives, please visit www.spxpe.com.

SPX Corporation reserves the right to incorporate our latest design and material changes without notice or obligation.

Design features, materials of construction and dimensional data, as described in this bulletin, are provided for your information only and should not be relied upon unless confirmed in writing.

Issued: 02 /2009 FH-1835